



# Large area diamond detectors for fast beam tagging applications in particle therapy

D. Dauvergne, A. Bes, G. Bosson, J. Collot, S. Curtoni, L. Gallin-Martel, ML. Gallin-Martel, A. Ghimouz, J.-Y. Hostachy, A. Lacoste, S. Marcatili, J-F. Muraz, F. Rarbi, O. Rossetto, M. Yamouni LPSC Grenoble

> M. Fontana, E. Testa **IPN** Lyon





M. Salomé, J. Morse, W. De Nolf **FSRF** 





L. Abbassi, T. Crozes, JF. Motte **NEEL Institute** 

D.Dauvergne - ADAMAS 2017





# Motivation (1/5) Need for in vivo ballistic control in particle therapy



Uncertainty sources :

Dose calculation: Planification (from CT images, RBE), patient positionning, anatomic variations during treatment, moving organs/tumor

 $\rightarrow$  Margins

Strategies:

Planification: dual-energy or proton CT, Monte Carlo simulations Online control: nuclear fragmentation products

- PET: a posteriori
- Prompt radiation: gamma, protons (ions heavier than protons)

#### Motivation (2/5) Time of Flight prompt-gamma imaging with 1D collimated camera



# Motivation (3/5)

# Spatial resolution issue

• Heterogeneities influence ion range and prompt-gamma yield



 Gamma imaging: compromise between spatial resolution and efficiency (statistics issue)

Proposed solution by IBA:

Knife-edge camera

(~2 cm spatial resolution)

[Richter, RaOn 2016]



• Ultra-fast timing resolution will improve spatial resolution

# Motivation (4/5) Compton imaging with beam hodoscope

CLaRyS collaboration (IPN Lyon, CPPM Marseille, LPC Clermont, LPSC Grenoble) Potentially higher detection efficiency than collimated devices

• Beam hodoscope: line-cone intersection



• TOF resolution < 500 ps  $\rightarrow$  real time Compton imaging

### Motivation (5/5) Prompt-gamma counting solutions

• Prompt-γ timing



- Average time and shape related to proton range
- 5mm range shift measurable with single spot
- Requires high timing resolution (< 1ns)</li>
- Limitations:
  - Cyclotrons
  - Bunch time spread
- Prompt-γ Peak Integral [Krimmer APL 2017]
  - 2-4 ns time window selection: PG issued from patient
  - Yield depends on energy deposited, beam position





#### [Petzoldt PMB 2016]

Both methods would benefit from fast and high-resolution beam-tagging system

### Beam tagging hodoscope development : LPSC MoniDiam project (within CLaRyS collaboration)

#### Existing development (CLaRyS) :

Array of scintillating fibres coupled to multichannel photomultiplier tubes (PMT). Fast readout with μTCA acquisition under test.



#### Limitations :

- Radiation hardness
- PMT count rate capability (10<sup>7</sup> cps per PMT)
- □ Time resolution 500 ps 1 ns



#### Foreseen development :

MoniDiam : diamond based hodoscope and its dedicated integrated fast read-out electronics for 100 ps resolution

#### **Diamond Assets :**

- Intrinsic radiation hardness
- □ Fast signal risetime enables timing precision of a few tens of ps
- Low noise

#### Issues :

- Cost
- Availability of large area

#### Solution : Assembly of double-side stripped diamond, polycrystalline or DOI

11/28/2017

### First tests: single disk-shape metallized diamonds





### Diamond detector characterization: test benches at LPSC



#### Beam test at GANIL : 95 MeV/u <sup>12</sup>C





### Beam test at GANIL : Time of flight measurements





#### Beam test at ESRF : XBIC source at 8.5 keV



#### Beam test at ESRF : XBIC source at 8.5 keV



### Stripped diamond characterization



NANOFAB Neel Institut Grenoble 100 nm Al deposition by UV lithography Wire bonding

Current preamplifier Detector assembly

**LPSC Grenoble** 

PCB design

11/28/2017

#### Beam test at ESRF : XBIC source at 8.5 keV



#### First results



#### **Timing resolution**



Best result:  $\sigma_t = 103 \text{ ps}$ 



# Front-End Electronics: Architecture

- 130nm CMOS TIA + Fast Discriminator
  - Radhard technology
  - Wide bandwidth, Low noise TIA

TIA Parameters	Value
A <sub>0</sub>	> 60 dB
F <sub>-3dB</sub>	1.2 GHz
Z <sub>in</sub>	20 – 50 Ω
V <sub>n,out</sub> (output noise)	< 1 mV <sub>RMS</sub>
Input Dynamic range	3 μA – 120 μA (<1% linearity)



1 channel FEE

# Front-End Electronics: Simulation

- Simulation parameters:
  - Extracted view + Noise tran
  - With bonding wires (2nH): Power supply, ground and input signal
  - Multi-gain discriminator
  - Jitter estimation: from 3 μA to 120 μA input signal





# Front-End Electronics: Layout



- 130nm CMOS
  - 8 channels FEE: TIA + Discriminator
  - Will be submitted on December 2017



1.485 x 1.2 mm<sup>2</sup>

### Conclusion

- Characterization of the performances of small and medium size detectors with sources, ions, and synchrotron
- Multi-strip detectors: a first prototype of 1 cm<sup>2</sup> has been developed and tested with discrete electronics
- Micro-electronics readout under development (technical collab. with LPC-Caen)
- > Framework:
  - ➢ Local: ESRF, NEEL:
    - local pole for detector and electronic devices
    - crystal processing and characterization
  - > National: LSPM, IPHC, CEA-LIST and CLaRyS collaboration (+CAL-Nice, Arronax...)
  - International: RD42

### Acknowledgements

The CLARA Canceropole (Oncostarter Project) is thanked.



The authors would like to acknowledge the ESRF for provision of synchrotron radiation facilities and would like to thank the ID21 beamline staff for their assistance with experiment MI-1243.

France HADRO

This work was supported by the Labex PRIMES (ANR-11-LABX-0063), FranceHadron (ANR-11-INBS-0007) and ANR MONODIAM-HE (ANR-089520).



grown.

The authors are grateful to Matthias Schreck from the Augsburg University for providing the LPSC laboratory with samples of diamond heteroepitaxially



saclay

Dominique Breton from the Laboratoire de l'Accélérateur Linéaire and Eric Delagnes from CEA Saclay are thanked for their implication in dedicated software development and technical support of the namely "wavecatcher" data acquisition system.